

PRO-SOUND

Public Address System



CS-30WP CS-20WP CS-10WP
COLUMN SPEAKER

Model	CS-30WP	CS-20WP	CS-10WP
Max power/Rated power	45W/30W	30W/20W	15W/10W
Line voltage	100V	100V	100V
Sensitivity(1m,1w)	92±3dB	91±3dB	88±3dB
Frequency response	170-15kHz	170-15kHz	170-15kHz
Dimension(mm)	548*106*75	405*106*75	262*106*75
Material	Aluminum	Aluminum	Aluminum
Weight(kg)	2.8	2	1.4
Speaker unit	6*2.5"	4*2.5"	2*2.5"

Model	CSL-206	CSL-306
Rated power	6W	6W
Line voltage	100V	100V
Sensitivity(1m,1w)	87±3dB	87±3dB
Frequency response	120-20kHz	120-20kHz
Dimension(mm)	Ø101*60	Ø103*80
Hole for mounting(mm)	Ø95	Ø95
Material	IRON	ABS
Weight(kg)	0.4	0.5
Speaker unit	2.5"	2.5"



CSL-206 CSL-306
CEILING SPEAKER



CSL-620 CSL-610 CSL-606
CEILING SPEAKER

Model	CSL-620	CSL-610	CSL-606
Max power/Rated power	20W	10W	6W
Line voltage	100V	100V	100V
Sensitivity(1m,1w)	91±3dB	91±3dB	91±3dB
Frequency response	100-13kHz	100-13kHz	100-13kHz
Dimension(mm)	Ø245*69	Ø200*65	Ø180*60
Hole for mounting	Ø220	Ø175	Ø155
Material	IRON	IRON	IRON
Weight(kg)	0.97	0.72	0.68
Speaker unit	6"	5"	4"