

AT standard rack cabine amplifier



AT standard size mixer amplifier (19" rack cabinet amplifiers)

AT-1650BT

Features

1. 3 MIC Inputs, 2 AUX inputs, and 1 AUX out for link. MIC1 with Priority.
2. Speaker outputs with line transformer 100V, 70V and 4-16Ohm.
3. Muting functions.
4. Individual volume control.
5. Low and High tone control.
6. LED level meter provided for a quick and easy Monitoring of the Sound level.
7. Short-circuit protection and Alarm.
8. MIC ECHO system.
9. USB port, SD card slot, FM tuner and Bluetooth.

AT standard rack cabine amplifier



|                          | AT-1120BT                                       | AT-1240BT | AT-1360BT | AT-1480BT | AT-1650BT | AT-11000BT                   |
|--------------------------|-------------------------------------------------|-----------|-----------|-----------|-----------|------------------------------|
| Power consumption        | 240W                                            | 480W      | 720W      | 960W      | 1300W     | 2000W                        |
| Rated Output Power       | 120W                                            | 240W      | 360W      | 480W      | 650W      | 1000W                        |
| Frequency response (AUX) | 100Hz~16000Hz±3dB                               |           |           |           |           |                              |
| DISTORTION (THD)         | <0.3% @ 1000Hz, 1/3 rated output power          |           |           |           |           |                              |
| Output                   | 4~16Ω, 70V, 100V                                |           |           |           |           |                              |
| Aux output               | 600Ω 250mV                                      |           |           |           |           |                              |
| Input                    | Mic1,2,3: 600Ω, 6.0mV                           |           |           |           |           |                              |
|                          | Aux1,2: 10KΩ, 250mV                             |           |           |           |           |                              |
| S/N ratio                | Mic1,2,3: ≥66dB                                 |           |           |           |           |                              |
|                          | Aux1,2: ≥70dB                                   |           |           |           |           |                              |
| Tone control             | Bass: ±10dB at 100Hz                            |           |           |           |           |                              |
|                          | Treble: ±10dB at 10000Hz                        |           |           |           |           |                              |
| Protection               | AC Fuse, DC Voltage, Overload and short circuit |           |           |           |           |                              |
| Muting function          | 0~30dB                                          |           |           |           |           |                              |
| Dimentions (Wx Hx D)     | 430(L) X 360(D) X 88(H) /mm                     |           |           |           |           | 430(L) X 360(D) X 132(H) /mm |
| Weight                   | 12Kg                                            | 14Kg      | 16Kg      | 18Kg      | 20Kg      | 22Kg                         |